

FIG. 1







FIG. 2




[illegible]

**FIG. 4**

**FIG. 5**



**FIG. 6**



7/23

FIG. 7





FIG. 7 is a graph of the function  $y = K_1 \left( \frac{1}{1 + \exp(-K_2 x)} - 0.5 \right)$  and its linear approximations  $y = K_3 x$  and  $y = K_4 x$ .

FIG. 8

00000350-12301  
FOEET 05200600



9/23

FIG. 9A





FIG. 9B



10/23

FIG. 10






FIG. 11



12/23

FIG. 12



**FIG. 13**




FIG. 13 is a perspective view of the assembly of FIG. 12, showing the base plate 61 and the rectangular block 62. The cylindrical component is shown in a perspective view, with a curved arrow indicating its rotation.

FIG. 14 is a perspective view of the assembly of FIG. 12, showing the base plate 61 and the rectangular block 62. The cylindrical component is shown in a perspective view, with a curved arrow indicating its rotation.

FIG. 15 is a perspective view of the assembly of FIG. 12, showing the base plate 61 and the rectangular block 62. The cylindrical component is shown in a perspective view, with a curved arrow indicating its rotation.

00000350 41204

FIG. 14




FIG. 15




FIG. 15 is a perspective view of the assembly 1, showing the base 1, the legs 2, the central opening 45, and the rotating plate 6. The dashed line indicates the plate 6 in a downward position.

FIG. 16 is a perspective view of the assembly 1, showing the base 1, the legs 2, the central opening 45, and the rotating plate 6. The dashed line indicates the plate 6 in a downward position.

FIG. 16





FIG. 16 is a perspective view of the assembly shown in FIG. 15, but with the central component (45) removed. The base plate (1) and legs (2) are shown in a perspective view.

FIG. 17 is a perspective view of the assembly shown in FIG. 15, but with the central component (45) removed. The base plate (1) and legs (2) are shown in a perspective view.




**FIG. 17**



00000350-11301

FIG. 18



000000760 44-38861-101

FIG. 19




FIG. 20




FIG. 21

URL

TROUBLE DB INPUT WINDOW

DATE OF OCCURRENCE  ~ 404

MODEL  ~ 401

SUBJECT  ~ 403

EQUIPMENT S/N  ~ 402

URGENCY  ~ 405


SYMPTOM  ~ 406

REMEDY  ~ 407

PROGRESS  ~ 408

410 411 412

[LINK TO RESULT LIST](#) [DATABASE](#) [SOFTWARE LIBRARY](#) [OPERATION GUIDE](#)

**FIG. 22**

FLOW CHART OF SEMICONDUCTOR DEVICE MANUFACTURING PROCESS

FIG. 23

